

FS425 : FOREGROUND MUSIC SPEAKER **NEW**

FS425 is a full range speaker, engineered to provide music and speech clarity for various installations such as restaurants, pubs, outdoor parks, etc. It is also suitable for outdoor installations with IP65 rating and can be mounted horizontally or vertically.

Be it a restaurant, pub or cafe, meeting room or lobby, FS425 shall be the exact candidate to choose from.

Packing information

FS340 : 370 (L) x 370 (W) x 600 (H) mm
 : 20.25 kg
 : 8 uts per carton



IP65
FS425
 4" 20W 100V

FS340 : FOREGROUND MUSIC SPEAKER

FS340 delivers smoothing sound with its 6" driver with tweeter. Available in 40W 100V line with power selector for level adjustment to suit area of installation. It can be installed vertically or horizontally, thanks to its flexible mounting bracket.

Be it a restaurant, pub or cafe, meeting room or lobby, FS340 shall be the exact candidate to choose from.

Packing information

FS340 : 480 (L) x 260 (W) x 450 (H) mm
 : 7.10 kg
 : 2 uts per carton



FS340
 6" 40W 100V



FS640 (Black / White)
 6" 40W 100V



FS420 (Black / White)
 4" 20W 100V

FS420 & FS640 : FOREGROUND MUSIC SPEAKER

Available in 4" and 6" of driver size complete with matching transformer, selectable power switch and mounting bracket. They are suitable for foreground soft music such as restaurants, shops and general sound reinforcement in meeting room, corridors, etc.

Packing information

FS420 : 440 (L) x 260 (W) x 370 (H) mm
 : 8.95 kg
 : 4 uts per carton
 FS640 : 415 (L) x 225 (W) x 360 (H) mm
 : 8.20 kg
 : 2 uts per carton

FS338 : FOREGROUND MUSIC SPEAKER

FS338 is built as multi purpose speaker, optimising the features of smooth and pleasant outlooks while maintaining the audio performance. Thus by its appearance and sound quality, it can be employed in most indoor venues.

It is driven by 2 x 4" PP speakers and a 1" tweeter with 40W 100V line power. It can also be driven directly from audio amplifier with 4 Ohm connections. Multiple power tapping is available via the rotary switch from 5 to 40W 100V line.

Installation is rather flexible due to its dual angle mounting bracket. They can be mounted in horizontal or vertical position. If wider coverage is required, then can be installed in horizontal array format, with two, three or 360 degree format via the optional mounting pole.



FS338
 2 x 4" 40W 100V

Packing information

FS338 : 555 (L) x 295 (W) x 165 (H) mm
 : 7.65 kg
 : 2 uts per carton

Technical Specifications

	FS420	FS425	FS640	FS340	FS338
SPEAKER					
Power rating	20W 100V		40W 100V		
Diameter	4" (100 mm)		6" (150 mm)	6" (150 mm)	2 x 4" (100 mm)
Speaker type	2 way speaker with tweeter				
Impedance (Ohm)	8				
Freq response @ 1KHz +/- 3dB	100 ~ 18 KHz	105 - 18KHz	70 ~ 18 KHz	70 ~ 16 KHz	
SPL @ 1W / m (+/- 3dB) 1 KHz	89 dB	87 dB	88 dB		87 dB
TRANSFORMER					
Tapping (100V line)	1.25 / 2.5 / 5 / 10 / 20W	10 / 20W	2.5 / 5 / 10 / 20 / 40W	5 / 10 / 20 / 40W	5 / 10 / 20 / 40W
Primary impedance (Ohm)	8K / 4K / 2K / 1K / 500 / 8	1K / 500	4K / 2K / 1K / 500 / 250 / 8	2K / 1K / 500 / 250 / 8	2K / 1K / 500 / 250 / 4
Secondary impedance (Ohm)	8				4
PHYSICAL					
Grille / enclosure	ABS enclosure with metal grille				
Overall size (W x H x D)	170 x 215 x 150 mm	170 x 245 x 150 mm	215 x 284 x 190 mm	209 x 585 x 195 mm	137 x 385 x 262 mm
Weight	1.95 kg	2.30 kg	3.70 kg	3.15 kg	3.50 kg
Colour	White and Black	Black	White and Black	Black	